Safety Data Sheets

Justice Court



RSC, Bowie

11/26/2019



Safety Data Sheet Index

Binder: RSC, Bowie - Justice Court

Product Name	CAS Number	Manufacturer	Version Date	Page
Compucessory Power Duster - Compucessory Power Duster	75-37-6	Falcon Safety Products, Inc	10/26/2017	3
Germ-X Hand Sanitizer - Germ-X Hand Sanitizer		Vi-Jon Incorporated	04/23/2008	9
Glade Air Freshener - All Fragrances - Glade Air Freshener - All Fragrances		S.C. JOHNSON WAX	02/05/1992	15
LYSOL BRAND DISINFECTANT SPRAY - ALL SCENTS - LYSOL BRAND DISINFECTANT SPRAY - ALL SCENTS		L & F PRODUCTS	09/30/1994	18



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 10/13/2015 Revision date: 10/26/2017 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Substance name : Computessory Power Duster

Product code : CCS24300/SPJR; CCS24305/SPXL; CCS24306/SPXL6; CCS24313/SPM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Dust Removal

1.3. Details of the supplier of the safety data sheet

Falcon Safety Products, Inc. 25 ImClone Drive Branchburg, NJ 08876 - USA

T (908) 707-4900

1.4. Emergency telephone number

Emergency number : (800) 498-7192

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US and **GHS-CA** classification

Flam. Aerosol 2

Press. Gas (Liquified Gas)

2.2. Label elements

GHS-US and **GHS-CA** labelling

Hazard pictograms (GHS-US/GHS-CA)





GHS02

02 GHS04

Signal word (GHS-US/GHS-CA)

Hazard statements (GHS-US/GHS-CA)

: Warning

 $: \ \ \, \text{Flammable aerosol. Contains gas under pressure; may explode if heated.}$

Precautionary statements (GHS-US/GHS-CA)

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

2.3. Other hazards

Do not store in enclosed vehicle.

2.4. Unknown acute toxicity (GHS US/GHS CA)

Not applicable.

SECTION 3: Composition/information on ingredients

3.1. Substance

Name	Product identifier	%
1,1-Difluoroethane	(CAS No) 75-37-6	100

3.2. Mixture

Not applicable.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and

act : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists. May cause frostbite.

10/13/2015 EN (English US) Page 1

Page 3 of 22

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.

First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.

Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause frostbite on contact with the liquid.

Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling. May cause frostbite on contact with the liquid.

Symptoms/injuries after ingestion : Not a normal route of exposure.

Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Water spray, water fog, dry chemical, alcohol resistant foam, carbon dioxide.

Unsuitable extinguishing media : None known.

Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol. Products of combustion may include, and are not limited to: oxides of

carbon, hydrofluoric acid, carbonyl fluoride.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

5.3. Advice for firefighters

Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area. Vapors are heavier than air

and may travel considerable distance to an ignition source and flash back to source of vapors.

Protection during firefighting Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA).

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to

unnecessary and unprotected personnel. Eliminate sources of ignition.

Methods and material for containment and cleaning up

For containment : Ventilate the area thoroughly, especially low lying areas (basements, workpits etc).

: Leave the product to evaporate. Provide ventilation. Methods for cleaning up

Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or

burn, even after use. Keep away from sources of ignition - No smoking.

: Do not spray on an open flame or other ignition source. Avoid contact with skin and eyes. Avoid Precautions for safe handling breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Provide local exhaust or general

room ventilation. When using do not eat, drink or smoke. Prevent the build-up of electrostatic charge. Use non-sparking tools.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions Keep out of the reach of children. Keep container dry and in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep in fireproof place.

Store in original container. Do not store in enclosed vehicle.

Specific end use(s)

Not available.

10/13/2015 EN (English US)

Page 4 of 22

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1,1-Difluoroethane (75-37-6)			
ACGIH	Not applicable.		
OSHA	Not applicable.		
NIOSH	Not applicable.		
IDLH	Not applicable.		

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Hand protection : Wear suitable gloves.

Eye protection : Safety glasses with side shields. Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection

must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Clear
Color : Colourless
Odor : Slight, ether-like
Odor threshold : No data available

pH : Neutral

Melting point No data available Freezing point : No data available -13 °F (- 25 °C) Boiling point Flash point : < 58 °F (<14.4 °C) Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) Flammable **Explosion limits** : 3.9-16.9 Explosive properties : No data available

Oxidizing properties : No data available

Vapor pressure : 5960 kPa at 77 °F (25 °C)

Relative density : 0.91

Relative vapor density at 20 °C : 2.4 at 77 °F (25 °C)

Specific gravity / density : 0.9
Solubility : Slightly

Partition coefficient: n-octanol/water : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

9.2. Other information

No additional information available.

10/13/2015 EN (English US) 3/6

Page 5 of 22

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition. Do not expose to temperatures exceeding 50 °C/ 122 °F.

10.5. Incompatible materials

Alkali and alkaline earth metals. Powdered metals. Powdered metallic salts.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, hydrofluoric acid, carbonyl fluoride.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Compucessory Power Duster				
LD50 oral rat	1500 mg/kg			
LD50 dermal rabbit	No data available			
LC50 inhalation rat	64000 ppm			
Skin corrosion/irritation	: Based on available data, the classification criteria are not met.			
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.			
Respiratory or skin sensitization	: Based on available data, the classification criteria are not met.			
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.			
Carcinogenicity	: Based on available data, the classification criteria are not met.			
Reproductive toxicity	: Based on available data, the classification criteria are not met.			
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.			
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.			
Aspiration hazard	: Based on available data, the classification criteria are not met.			
Symptoms/injuries after inhalation	: May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.			
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause frostbite on contact with the liquid.			
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. May cause frostbite on contact with the liquid.			
Symptoms/injuries after ingestion	: Not a normal route of exposure.			

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Compucessory Power Duster	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Compucessory Power Duster	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available.

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

10/13/2015 EN (English US) 4/6

Page 6 of 22

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

UN-No. (DOT) : UN1030

Proper Shipping Name (DOT) : 1,1-Difluoroethane

Transport hazard class(es) (DOT) : 2.1

Hazard labels (DOT) :



Packaging Exceptions : Falcon Safety Products has been granted a DOT special permit. A copy of DOT Special Permit

SP-11516 can be obtained by calling Falcon Safety Products, Inc. at 908-707-4900.

Transportation of Dangerous Goods (TDG)

In accordance with TDG

UN-No.(TDG) : UN1030

Proper Shipping Name (TDG) : 1,1-Difluoroethane

Class (TDG) : 2.1

Hazard labels (TDG) :



Packaging Exceptions : TDG Canada: Falcon Safety Products has been granted Equivalency Certificate SU 9211 (ren.

1) by the TCSS, TDGD to offer for transport by road, rail and marine.

Transport by sea

UN-No. (IMDG) : UN1030

Proper Shipping Name (IMDG) : 1,1-DIFLUOROETHANE (REFRIGERANT GAS R 152a)

Class (IMDG) : 2.1

Air transport

UN-No. (IATA) : UN1030

Proper Shipping Name (IATA) : 1,1-Difluoroethane

Class (IATA) : 2.1

Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

1,1-Difluoroethane (75-37-6)

Listed on the Canadian DSL (Domestic Sustances List)

15.2. US State regulations

Compucessory Po	ower Duste	r
-----------------	------------	---

State or local regulations

This product does not contain a chemical known to the State of California to cause cancer,

10/13/2015 EN (English US) 5/6

Page 7 of 22

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Compucessory Power Duster	
	birth defects or other reproductive harm.

SECTION 16: Other information

Date of issue : 10/13/2015 : 10/26/2017 Revision date Other information : None.

Mexico Classification:



Blue = Health Red = Flammability Yellow = Reactivity White = Special

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

10/13/2015 EN (English US) Item Number: 028 Page 1 04/23/2008 of 6

Material Safety Data Sheet

314-427-1000

1-800-424-9300

In Case of Spill Emergency Contact:

Chemtrec:



Section 1: PRODUCT AND COMPANY IDENTIFICATION

Vi-Jon Incorporated 8515 Page Avenue Saint Louis, MO 63114

Product Name: Germ-X Hand Sanitizer

Product Code: 028

Product Use: Hand Sanitizer Issue Date: 04/23/2008 Supersedes Date: July 2007

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Keep out of reach of children. Appearance/Odor: Clear gel with alcohol/citrus odor.

WARNING:

Flammable (ethyl alcohol and isopropyl alcohol)

Target (ethyl alcohol and isopropyl alcohol) respiratory system, skin, eyes, CNS, liver, blood and reproductive system.

Potential Health Effects: See Section 11 for more information.

Symptoms of Exposure:

Inhalation: May cause irritation of the respiratory tract. Ingestion: May cause nausea, vomiting and diarrhea.

Eyes: May cause irritation to the eyes.

Skin: None expected.

This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

This material contains component s that are considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Environmental Effects: See Section 12 for more information.

Item Number: 028 Page 2 04/23/2008 of 6

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS#	% by Wt.
Ethyl Alcohol	64-17-5	59%
Isopropyl Alcohol	67-64-0	3%

Section 4: FIRST AID MEASURES

Emergency first aid procedures by route of exposure:

Inhalation: If symptoms are experience, remove source of contamination or move victim to

fresh air. If affected person is not breathing, apply artificial respiration. If

breathing is difficult, give oxygen. Get medical attention.

Ingestion: Do not induce vomiting. If the material is swallowed, get medical attention or

advice.

Skin: If irritation is experienced, flush with water. If irritation persists, get medical

attention.

Eyes: Immediately flush eyes with water for at least 15 minutes while holding eyelids

open. If symptoms persist, get medical attention.

Section 5: FIRE FIGHTING MEASURES

Flash Point: 71°F (21.6°C) Method Used: ASTM D-93

Lower Flammable Limit: 3.3 (Volume % in air) Upper Flammable Limit: 19.0 (Volume % in air)

Auto Ignition: (Ethyl Alcohol) 363°C

Flammability Classification: Flammable Liquid IB

Extinguishing Media: Use methods appropriate for the surrounding fire. Consider water spray or fog, carbon dioxide, dry chemical powder, or alcohol resistant foam.

Products of Combustion: Upon decomposition this product may emit carbon dioxide, carbon monoxide and/or low molecular weight hydrocarbons.

Fire Fighting Equipment/Instructions: Wear protective clothing and equipment suitable for the surrounding fire, including helmet, facemask, and self contained breathing apparatus.

NFPA Rating: Health:2 Fire: 3 Reactivity:0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: For large spills wear gloves, safety glasses and when levels exceed OSHA PEL use appropriate NIOSH approved respiratory protection. Keep unnecessary personnel away. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.

Environmental Precautions: Prevent discharge to open waters.

Method for Containment: Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth.

Methods for Clean-Up: Ventilate area of leak or spill. Use spark-proof tools to sweep or scrape up and containerize in approved chemical waste container. Wash spill area with water.

Item Number: 028 Page 3
04/23/2008 of 6

Section 7: HANDLING AND STORAGE

Handling: Keep away from heat, sparks and flame. Prevent contact with eyes. Avoid

inhalation.

Storage: Keep the container tightly closed and in a cool, well ventilated place.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Ethyl Alcohol (64-17-5)

ACGIH: 1,000 ppm TWA

OSHA: 1,000 ppm TWA; 1,900 mg/m3 TWA

Isopropyl Alcohol (67-63-0)

ACGIH: 200 ppm TWA

OSHA: 400 ppm TWA; 980 mg/m3 TWA

Engineering Controls: Normal room ventilation is usually adequate under normal use.

Personal Protective Equipment (PPE)

Eye/Face Protection: None needed under normal use. **Skin Protection**: None needed under normal use. **Respiratory Protection**: None needed under normal use.

General Hygiene Considerations: None needed under normal use.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Color: Clear Translucent

Odor: Alcohol/Citrus Physical State: Gel pH: Not Available.

Vapor Density: (Ethyl Alcohol) 1.6 Boiling Point: (Ethyl Alcohol) 78.5°C

Vapor Pressure: (Ethyl Alcohol) 57.3 hPa at 20°C

Melting Point: (Ethyl Alcohol) -114.1°C

Freezing Point: Not Available Flash Point (see section 5)

Flammability Properties (see section 5)

Solubility (in water): Soluble

Specific Gravity @ 25°C: 0.88-0.92 Evaporation Rate: Not Available

Octanol/Water partition coefficient (Kow): (Ethyl Alcohol): - 0.32

Auto-ignition temperature: (Ethyl Alcohol) 363°C Decomposition temperature: Not Available

Item Number: 028 Page 4
04/23/2008 of 6

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal ambient temperatures 70°C (21°C)

Condition to Avoid: Avoid excessive heat or sources of ignition.

Incompatible Materials: This product reacts with strong acid, strong bases, and oxidizing

agents.

Hazardous Decomposition: upon decomposition, this product evolves carbon monoxide, carbon dioxide, and/or low weight hydrocarbons.

Hazardous Reactions: Hazardous polymerization will not occur.

Section 11: TOXICOLOGY INFORMATION

ACUTE EFFECTS:

A: General Product information

Product contains ethyl alcohol and isopropyl alcohol.

B: Component Analysis LD50

Ethyl Alcohol (64-17-5) Oral LD50 Rat: 7060 mg/kg

Isopropyl Alcohol (67-63-0)

Inhalation LC50 Rat: 72.6 mg/L/4H Oral LD50 Rat: 4396 mg/kg Dermal LD50 Rat: 12800 mg/kg Dermal LD50 Rabbit: 12870 mg/kg

CHRONIC EFFECTS:

Component

Ethyl Alcohol (64-17-5)

Carcinogenicity: ACGIH A4 – Not Classifiable as a Human Carcinogen

Neurotoxicity: This product contains ethyl alcohol, a central nervous system target.

Mutagenicity: No information available for product. **Reproductive**: No information available for product.

Developmental: Ethyl alcohol is a developmental toxin when consumed during

pregnancy.

Target Organs: When consumed, ethyl alcohol can target the

respiratory system, skin, eyes, CNS, liver, blood and reproductive system.

Isopropyl Alcohol (67-63-0)

Carcinogenicity: ACGIH A4 – Not Classifiable as a Human Carcinogen

Neurotoxicity: This product contains isopropyl alcohol, a central nervous system target.

Mutagenicity: No information available for product. **Reproductive**: No information available for product. **Developmental**: No information available for product.

Target Organs: skin, eyes, CNS, Kidney, Developmental and respiratory system.

Item Number: 028 Page 5 04/23/2008 of 6

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Ethyl Alcohol (64-17-5)

96 hour LC50 Oncorhynchus mykiss: 12,900 mg/L (flow-through) (30days old)

96 hour LC50 Pimephales promelas 14.2 mg/L

5 min EC50 Photobacterium phosphoreum: 35,470 mg/L 30 min EC50 Photobacterium phosphoreum: 34,634 mg/L

48 hour EC50 Daphnia magna: 9,268 mg/L 24 hour EC50 Daphnia magna: 10,800 mg/L

Ecotoxicity: Isopropyl Alcohol (67-63-0)

96 Hr EC50 Scenedesmus Subspicatus: >1000 mg/L

72 Hr EC50 Scenedesmus subspicatus:>1000 mg/L

96 Hr LC50 Pimephales promelas: 9640 mg/L [flow through]

96 Hr LC50 Pimephales promelas: 94900 mg/L [flow through] (29 days old) 96 Hr LC50 Pimephales promelas: 61200 mg/L [flow through] (31 days old)

5 min EC50 Photobacterium phosphoreum: 35390 mg/L

48 Hr EC50 Daphnia magna: 13299 mg/L

Section 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state, and local regulations.

Section 14: TRANSPORTATION INFORMATION

Shipping Name: Consumer Commodity ORM-D

Proper Shipping Name for Non-Consumer Commodity: Ethyl Alcohol Solutions, 3, UN1170, PGIII.

IMDG: UN1170, Ethanol Solutions (Ethyl Alcohol Solution), Class 3, PG II (21.6C cc) EmS # F-E S-D, Limited Quantity

Section 15: REGULATORY INFORMATION

Ethyl alcohol and isopropyl alcohol, components of this product, are on the TSCA inventory.

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

This material contains ethyl alcohol a developmental toxicity when in alcoholic beverages.

The following components appear on one or more of the following state hazardous substance lists:

Component	CAS#	CA	MA	MN	NJ	PA
Isopropyl Alcohol	67-63-0	YES	YES	YES	YES	YES
Ethyl alcohol	64-17-5	YES	YES	YES	YES	YES

Item Number: 028 Page 6 04/23/2008 of 6

Section 16: Other Information

Prepared by: Vi-Jon Inc.

Disclaimer:

The information and recommendations contained in the Material Safety Data Sheet (MSDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date hereof.

Vi-Jon, however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will be required to make their own determination as to its suitability for their purposes prior to use. In no event will Vi-Jon be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information. User assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE, ARE MADE BY VI-JON HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance which is the subject matter of this MSDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to product liability, rests solely upon the purchaser thereof.

This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.

S.C. Johnson Wax
Racine, Wisconsin 53403-5011
Phone: (414) 631-2777
Racine, Wisconsin 53403-5011
Phone: (414) 631-2777
Remargency Phone: (800) 228-5635
Remargency Phone: (800) 228-5635
Remargency Phone: Extension 092
Remargency Phone: Extension 092

MATERIAL SAFETY DATA SHEET

SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: PRODUCT CODE: 10545-1

CHEMICAL OR COMMON NAME: PATE ISSUED. SUPERSEDES: MSDS SECTIONS WITH CHANGES: PREPARED BY:

PRODUCT NAME: GLADE AIR FRESHEN	IER - ALL I	FRAGRANCES	į			PRODUCT CODE: 10545-1
THEMICAL OR COMMON NAME:	DATE ISSUED.			CTIONS WITH C	********	
NA		10/30/87	MSD2 2E	CTIONS WITH C	MANGES:	PREPARED BY:
	02/03/92	10/30/07	+			Terry A. Meyers
	. 	<u> </u>	<u>. </u>			Chemical Info. Adm.
	SECTIO	ON II-INGF	REDIE	NT INFOR	MATIO	NI
INGRE	DIENTS			WEIGHT	¥	EXPOSURE LIMIT
ISOBUTANE\PROPANI	(CAS#			25 35		OPPM (OSHA PEL)
75-28-5,74-98-6)	, ,,			23 ,3		OPANE)
WATER				65-75	NA.	
				03-73	į	
D.T.O.D.	**************************************	SECTION I	I-PH	YSICAL D	ATA	
WITH	ENSED AS A FRAGRANT	SPRAY MIS ODOR	ST SPEC	CIFI. GRAVITY	(H20-1):	0.8
VAPOR PRESSURE (mm Hg):	ND		PER	CENT VOLATILE	BA AOTOM	E (%); NA
SCLUBILITY IN WATER - AI	preciable		VAPO	OR DENSITY (A	r=1);	ND
FREEZING COINT (°F) NI	· · · · · · · · · · · · · · · · · · ·		BOI	LING POINT POL	N	D
rh ND						
TH ND			EVAI	PORATION RATE	(Butyl A	cctate-1): NA
VOC (as packaged, minus H20	: ND		THE	ORETICAL VOC	ilh/gall:	ND
	SECTION I	V-FIRE ANI	EXP	LOSION I	NFORM	ATION
PLASH FOINT (*F) (Method Use	ed): UND	ER 20 (TCC)	(PR	OPELLANT)	
FLAMMABLE LIMITS: ND						
EXTINCUISHING MEDIA: FO	oam. 002.	Dry Chemic	cal.	Water Fo	g.	
		· · · · · · · · · · · · · · · · · · ·				
SPECIAL FIREFIGHTING PROCED	mes NOT	mal fire :	tight	ing proc	edure	s may be used. Fight
rire from maximum	n distance	or protec	cted	area. Co	ol an	d use caution when
approaching or na	andling fi	re-exposed	d con	tainers.		
UNUSUAL PIRE AND EXPLOSION	HAZARDS N	o special	haza	rds know	n.	
	SE	CTION V-HI	2 A T . TTU	UA 7 A DID	רא תיא	4-1-
PRIMARY ROUTE OF ENTRY	NA NA		TUTIO	MALARD	DUIN	
SIGNS AND SYMPTOMS: NA				·		
FIRST AID PROCEDURES:	<u>√</u>					
APPLEAL COMPANY		·· · ···				
PEDICAL CONDITIONS GENERALL	KECOGNIZED AS E	BEING AGGRAVATED	BA SXBC	CSURF		

MATERIAL SAFET	Y DATA SHEET Page 2
S.C. Johnson Wax GI	ADE AIR FRESHENER - ALL FRAGRANCES
OKOK HAWA Chwash	oduct Number: 10545
Racine, Wisconsin 53403 Se	rial Number: 1
SECTION VI-REAC	ጥፐ Vፕጥሃ ቡልጥል
stable Stable	
STABILITY-CONDITIONS TO AVOID: None known	
INCOMPATIBILITY. None known	
HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to combustion.	tire, produces normal products of
HAZARDOUS POLYMERIZATION: Will not occur.	
HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID. None kno	wn
SECTION VII-SPILL OR	LEAK PROCEDURES
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Rinse affected area thoroughly with wate WASTE DISPOSAL INFORMATION: Recycle empty aerosc	Fliminate all ignition courses
waste disposal information: Recycle empty aeroso center. Use up package or give to someon	l can to nearest steel recycling le who can.
SECTION VIII-SPECIAL PROT	ECTION INFORMATION
RESPIRATORY PROTECTION: No special requirements	under normal use conditions.
ventilation: General room ventilation adequa	te.
PROTECTIVE GLOVES: No special requirements un	der normal use conditions.
EYE PROTECTION: No special requirements under	normal use conditions.
OTHER PROTECTIVE MEASURES: NSR	
SECTION IX-SPECIA	L PRECAUTIONS
PRECAUTIONARY LABELING: CAUTION: CONTENTS UNDER RADIATOR OR KEEP WHERE TERPERATURE WILL BURST. DO NOT PUNCTURE OR THROW IN FIRE.	EXCEED 120 F AS CONTAINER MAY
OTHER HANDLING AND STORAGE CONDITIONS Keep out of pressurize, cut, heat, weld or expose cooccur.	reach of children. Do not ontainer to flame; explosion could
SECTION X-ADDITIONA	L INFORMATION
ADDITIONAL INFORMATION: FACTORY MUTUAL LEVEL 1	AFROSOL
SECTION XI-TRANSPORTAT	ION INFORMATION
DOT MASS:	
DOT #	
SHEPPING NAME	
DOT NOTES	

MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin

53403

Product Number: 10545

Serial Number: 1

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined. The information herein in given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be a accordance with applicable Federa. State, and local laws and regulations. The information contained in this form is confidential and is submitted so ely for your organization's internal use.

REMATERIAL SAFETY DATA SHEET

LYSOL(R*) BRAND DISINFECTANT SPRAY - ALL SCENTS

REV. DATE: 09/30/94

L & F PRODUCTS 225 SUMMIT AVENUE MONTVALE, NJ 07645

Riverview Regional Medical Center

TELEPHONE NUMBER: (201)573-5700 (24 HRS)

EMERGENCY CONTACT: CHEMTREC-FOR DOT EMERGENCIES ONLY

EMERGENCY PHONE NUMBER: (800)424-9300

-----SECTION #1 - IDENTIFICATION -----

PRODUCT: LYSOL(R*) BRAND DISINFECTANT SPRAY - ALL SCENTS

EPA REG. NO.: 777-53

SPECIAL HAZARDS: FLAMMABLE. CONTENTS UNDER PRESSURE.

HAZARD RATINGS:

NFPA

HEALTH: 1 SLIGHT FIRE: LEVEL 1 AEROSOL REACTIVITY: 0 NEGLIGIBLE

HMIS

HEALTH: 1 SLIGHT

FLAMMABILITY: 3 SERIOUS* REACTIVITY: 0 MINIMAL

*THIS IS A LEVEL 1 AEROSOL. THIS RATING APPLIES TO THE PRODUCT CONCENTRATE

AND NOT THE FINISHED, SEALED AEROSOL PRODUCT.

PRODUCT DESCRIPTION: AEROSOL DISINFECTANT

FORMULA NO.	PRODUCT NO.	SCENT
Z2381	01-C0111-000	ORIGINAL
56-036	01-C0508-000	ORIGINAL
4Z1961	01-C0115-000	FRESH
73-004	01-C0505-000	FRESH
7Z1511	01-C0123-000	FRESH
8Z0531	01-C0131-000	LIGHT (I.C.)
3AB1122	01-C0134-000	LIGHT (I.C.)
Z047A-10	01-C0144-000	COUNTRY
76-054B	01-C0673-000	COUNTRY
AE3-090B	01-C0335-000	MOUNTAIN
75-013B	01-C0339-000	MOUNTAIN
75-018	01-C0736-000	BAYBERRY PINE

THIS PRODUCT IS A REGISTERED PESTICIDE. USE OF THIS PRODUCT IN A MANNER NOT CONSISTENT WITH THE LABEL INSTRUCTIONS IS A VIOLATION OF FEDERAL LAW.

-----SECTION #2 - HAZARDOUS CHEMICAL COMPONENTS -----

Return to Index

COMPONENT: CARBON DIOXIDE (AS PROPELLANT)

CAS NUMBER: 124-38-9 PERCENT OF MIXTURE: 4.0

ACGIH TLV-STEL: 30,000 PPM ACGIH TLV-TWA: 5000 PPM OSHA PEL-TWA: 5,000 PPM

COMPONENT: ETHANOL

CAS NUMBER: 64-17-5 PERCENT OF MIXTURE: 79.0

ACGIH TLV-TWA: 1000 PPM OSHA PEL-TWA: 1000 PPM

COMPONENT: ORTHO-PHENYLPHENOL

CAS NUMBER: 90-43-7 PERCENT OF MIXTURE: .1

NO EXPOSURE LIMITS ESTABLISHED

BY ACGIH OR OSHA

-----SECTION #3 - PHYSICAL DATA -----

BOILING POINT: NOT APPLICABLE DEG C

VAPOR PRESSURE: 95 - 105 PSIG

VAPOR DENSITY (AIR=1): >1

SPECIFIC GRAVITY: 0.835 @ 25 DEG C (CONC)

SOLUBILITY (H2O): COMPLETE

PH: APPROX. 10 AT A CONCENTRATION OF: 50%

APPEARANCE:

AEROSOL CONTAINER

-----SECTION #4 - FIRE FIGHTING & EXPLOSION DATA -----

FLASH POINT: 70 DEG F TCC (CONCENTRATE)

LOWER EXPLOSIVE LIMIT (%): NOT DETERMINED UPPER EXPLOSIVE LIMIT (%): NOT DETERMINED

FIRE AND EXPLOSION HAZARDS

FLAMMABLE. CONTENTS UNDER PRESSURE. DO NOT USE NEAR HEAT, SPARK OR FLAME. DO NOT PUNCTURE OR INCINERATE CONTAINER. EXPOSURE TO TEMPERATURES ABOVE 130 DEG F MAY CAUSE BURSTING.

EXTINGUISHING MEDIA

WATER SPRAY, FOAM, DRY CHEMICAL OR CARBON DIOXIDE. USE MEDIA SUITABLE FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

SPECIAL FIRE FIGHTING INSTRUCTIONS

WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE EQUIPMENT APPROPRIATE FOR FIGHTING A TYPICAL CHEMICAL FIRE. MOVE CONTAINERS AWAY FROM FIRE IF POSSIBLE AND SAFE TO DO SO. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS. PROVIDE SHIELDING FOR VENTING, RUPTURING OR BURSTING CONTAINERS.

-----SECTION #5 - EXPOSURE EFFECTS AND FIRST AID -----

Return to Index

ROUTE OF EXPOSURE - INHALATION:

NONE EXPECTED. SUSCEPTIBLE INDIVIDUALS MAY EXPERIENCE DIZZINESS, DROWSINESS, NAUSEA AND VOMITING IF EXPOSED TO EXTREMELY HIGH CONCENTRATIONS OF THE VAPORS.

FIRST AID - INHALATION: IF REQUIRED, REMOVE TO FRESH AIR.

ROUTE OF EXPOSURE - SKIN: NONE EXPECTED.

FIRST AID - SKIN: RINSE WITH WATER.

ROUTE OF EXPOSURE - EYES: AVOID CONTACT WITH EYES.

FIRST AID - EYES:

IMMEDIATELY FLUSH EYES THOROUGHLY WITH WATER, REMOVE ANY CONTACT LENSES AND CONTINUE TO FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

ROUTE OF EXPOSURE - INGESTION:

INGESTION IS VERY UNLIKELY THROUGH THE NORMAL ANTICIPATED USE OF THIS PRODUCT. INGESTION OF SMALL QUANTITIES IS NOT EXPECTED TO CAUSE ANY SIGNIFICANT ADVERSE EFFECTS. AVOID CONTACT WITH FOOD.

FIRST AID - INGESTION: CONTACT A PHYSICIAN.

MISCELLANEOUS TOXICOLOGICAL INFORMATION:

CARCINOGENICITY: NTP: NO IARC: NO OSHA: NO

HEALTH CONDITIONS AGGRAVATED BY EXPOSURE:

NONE KNOWN

-----SECTION #6 - REACTIVITY & POLYMERIZATION -----

STABILITY: STABLE

CONDITIONS TO AVOID (STABILITY): AVOID TEMPERATURES ABOVE 130 DEG F

INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING THERMAL DECOMPOSITION.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

-----SECTION #7 - SPILL, LEAK, & DISPOSAL PROCEDURES -----

STEPS TO BE TAKEN IN THE EVENT OF SPILLS, LEAKS, OR RELEASE: FOR LARGE SPILLS DUE TO RUPTURED CONTAINERS, ELIMINATE ALL SOURCES OF IGNITION AND VENTILATE THE AREA WITH EQUIPMENT RATED FOR USE IN FLAMMABLE

Retinit Remembers. Collect Liquid and Store in Metal Containers for Disposal.

WASTE DISPOSAL METHODS:

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

CONTAINER DISPOSAL:

REPLACE CAP AND DISCARD IN TRASH. DO NOT PUNCTURE OR INCINERATE. DO NOT REUSE EMPTY CONTAINER.

OTHER ENVIRONMENTAL INFORMATION:

NONE OF THE INGREDIENTS IN THIS PRODUCT MEET THE REPORTING REQUIREMENTS OF THE SARA TITLE III, SECTION 313 LIST OF TOXIC CHEMICALS.

-----SECTION #8 - SPECIAL PROTECTIVE MEASURES -----

VENTILATION: NONE REQUIRED.

EYE PROTECTION: NONE REQUIRED.

SKIN PROTECTION: NONE REQUIRED.

RESPIRATORY PROTECTION: NONE REQUIRED.

-----SECTION #9 - SPECIAL PRECAUTIONS - STORAGE & HANDLING -----

STORAGE & HANDLING CONDITIONS:

STORE IN ORIGINAL CONTAINER IN AREAS INACCESSIBLE TO SMALL CHILDREN. FLAMMABLE. CONTENTS UNDER PRESSURE. DO NOT USE NEAR FIRE, SPARKS OR FLAME. EXPOSURE TO TEMPERATURES ABOVE 130 DEG F MAY CAUSE BURSTING.

-----SECTION #10 - SHIPPING INFORMATION -----

PROPER SHIPPING NAME: CONSUMER COMMODITY

DOMESTIC COMMERCE - SURFACE ONLY HAZARD CLASS: ORM-D

STATE REGULATED COMPONENTS

COMPONENT: CARBON DIOXIDE (AS PROPELLANT)

CAS NUMBER: 124-38-9 PERCENT OF MIXTURE: 4.0

STATE REGULATIONS: ILL MAS NJW PAW

COMPONENT: ETHANOL

CAS NUMBER: 64-17-5 PERCENT OF MIXTURE: 79.0

STATE REGULATIONS: ILL MAS NJS NJW PAW P65

COMPONENT: ORTHO-PHENYLPHENOL CAS NUMBER: 90-43-7 PERCENT OF MIXTURE: .1

STATE REGULATIONS: NJE NJW

ILL - ILLINOIS TOXIC SUBSTANCE

MAS - MASSACHUSETTS HAZARDOUS SUBSTANCE

NJE - NEW JERSEY ENVIRONMENTAL HAZARDOUS SUBSTANCE

NJS - NEW JERSEY SPECIAL HEALTH HAZARDOUS SUBSTANCE

NJW - NEW JERSEY WORKPLACE HAZARDOUS SUBSTANCE

PAE - PENNSYLVANIA ENVIRONMENTAL HAZARDOUS SUBSTANCE

Product code 1647033

Document 1647033

Retundo Indernnsylvania special hazardous substance

PAW - PENNSYLVANIA WORKPLACE HAZARDOUS SUBSTANCE P65 - CALIFORNIA PROPOSITION 65