Safety Data Sheets

Library



Portal

11/07/2018



Safety Data Sheet Index Binder: Portal - Library

Product Name	CAS Number	Manufacturer	Version Date	Page
ABC Dry Chemical Fire Extinguishant - ABC Dry Chemical Fire Extinguishant		AMEREX CORPORATION	03/13/2018	3
PURELL Hand Sanitizer - PURELL Hand Sanitizer		GOJO Industries, Inc.	03/19/2015	15



SAFETY DATA SHEET

Section 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Other Identifiers: Product Code(s): Model Code(s) of Extinguishers:

Recommended Use:

Manufacturer: Internet Address: Address:

Company Telephone: E-mail Address: Emergency Contacts:

Revised:

ABC Dry Chemical Fire Extinguishant Multi-purpose Dry Chemical CH555, F13, F11 402, IS 18ABC, IS35ABC, IS 45ABC, 13ABC, V25ABC, VH25ABC, V30ABC, VH30ABC, V50ABC, V550ABC, VS75ABC, V250ABC Fire suppression, not for human or animal drug use. AMEREX CORPORATION www.amerex-fire.com

7595 Gadsden Highway, P.O. Box 81 Trussville, AL 35173-0081 (205) 655-3271 info@amerex-fire.com Chemtrec 1(800) 424-9300 or (703) 527–3887 March 13, 2018

Section 2. HAZARDS IDENTIFICATION

GHS – Classification

Health	Environmental	Physical
Acute Toxicity: Category 5	None	None
Skin Corrosion/Irritation: Category 3	None	None
Skin Sensitization: NO	None	None
Eye: Category 2A	None	Warning
STOT – Category 3	None	Warning
Carcinogen: Category None	None	None

GHS – Label Symbol(s):



If Pressurized: Gas Under Pressure

GHS – Words(s):

Warning

Other Hazards Not Resulting in Classification: Mica may contain small quantities of quartz (crystalline silica). Prolonged exposure to respirable crystalline silica dust at concentrations exceeding the occupational exposure limits may increase the risk of developing a disabling

lung disease known as silicosis. IARC found limited evidence for pulmonary carcinogenicity of crystalline silica in humans. In the case of normal use of this product, exposure to silica should be nil.

The attapulgite clay used in this product has a fiber length of less than 5um; therefore, the clay is not considered to be carcinogenic in animals or humans.

GHS Hazard	GHS Codes(s)	Code Phrase(s)	
Physical	H229	*- Contents under pressure; may explode if heated.	
Health	H303	May be harmful if swallowed	
	315	Causes skin irritation	
	319	Causes serious eye irritation	
	335	May cause respiratory irritation	
Environmental	None		
Precautionary:			
General	P101	If medical advice is needed, have product container or label at hand	
Prevention	P251	Do not pierce or burn, even after use.	
	261	Avoid breathing dust/fumes/gas/mist/vapours/spray.	
	264	Wash exposed skin thoroughly after handling.	
	280	Wear protective gloves/protective clothing/eye protection/face protection.	
Response	P312	Call a doctor if you feel unwell.	
	321	Specific treatment (see Section 4. First Aid Measures)	
	362	Take off contaminated clothing.	
	302+352	IF ON SKIN: Wash with plenty of water.	
	304+340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
	305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if	
		present and easy to do – continue rinsing.	
	332+313	If skin irritation occurs: Get medical advice/attention.	
	342+311	If experiencing respiratory symptoms: Call a doctor.	
	337+313	If eye irritation persists get medical advice/attention.	
Storage	P410 +403	*- Protect from sunlight. Store in well-ventilated place.	
Disposal	P501	Dispose of contents through a licensed disposal company. Contaminated container should	
		be disposed of as unused product.	

GHS – Hazard Phrases

*- If under pressure

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	EC No.	REACH Reg. No.	CAS-No.	Weight %	Classification
Mono-ammonium phosphate	231-764-5	01-2119488166-29	7722-76-1	80-98	NA
Attapulgite clay	601-805-5	Not Available	12174-11-7	3-16	NA
Mica- potassium aluminum silicate	310-1276	Not Available	12001-26-2	1-2	NA
Silicone oil methyl hydrogen polysiloxane	613-152-3	Not Available	63148-57-2	<1	NA
Calcium carbonate	207-439-9	Not Available	1317-65-3	<1	NA
Amorphous silica precipitated synthetic zeolite	231-545-4	01-2119379499-16- 0036	7631-86-9	<1	NA
Yellow 14 pigment – di-azo dye	226-789-3	Not Available	5468-75-7	<1	NA

Emergency overview:

Light yellow, fine solid powder, odorless.

Adverse health effects and symptoms:

Mild irritant to the respiratory system. Irritant to eyes, and skin. Symptoms may include coughing,

shortness of breath, and irritation of the lungs, eyes, and skin. Ingestion, although unlikely, may cause cramps, nausea and diarrhea.

Section 4. FIRST AID MEASURES

Eye Exposure:	May cause irritation. Irrigate eyes with water and repeat until pain free. Seek medical attention if irritation develops, or if vision changes occur.
Skin Exposure:	May cause skin irritation. In case of contact, wash with plenty of soap and water. Seek medical attention if irritation persists.
Inhalation:	May cause irritation, along with coughing. If respiratory irritation or distress occurs remove victim to fresh air. Seek medical attention if irritation persists.
Ingestion:	Overdose symptoms may include numbness or tingling in hands or feet, uneven heart rate, paralysis, feeling faint, chest pain or heavy feeling, pain spreading to the arm or shoulder, nausea, diarrhea, sweating, general ill feeling, or seizure (convulsions). If victim is conscious and alert, give 2-3 glasses of water to drink. If conscious, do not induce vomiting. Seek immediate medical attention. Do not leave victim unattended. To prevent aspiration of swallowed product, lay victim on side with head lower than waist.
Medical conditions possibly	
aggravated by exposure:	Inhalation of product may aggravate existing chronic respiratory problems such as asthma, emphysema, or bronchitis. Skin contact may aggravate existing skin disease. Chronic overexposure may cause pneumoconiosis ("dusty lung" disease).

Section 5. FIRE-FIGHTING MEASURES

Flammable Properties: Flash Point: Suitable Extinguishing Media:

Hazardous Combustion Products:

Not flammable Not determined Non-combustible. Use extinguishing media suitable for surrounding conditions. Carbon oxides

Explosion Data: Sensitivity to Mechanical Impact: Sensitivity to Static Discharge: Unusual fire/explosion hazards:

Protective Equipment and Precautions for Firefighters:

Not sensitive Not sensitive In a fire this material may decompose, releasing oxides of carbon, potassium and nitrogen (see Section 10).

As in any fire, wear self-contained breathing apparatus pressure-demand. NIOSH (approved or equivalent) and full protective gear.

Section 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid contact with skin, eyes, and clothing. Minimum - safety glasses, gloves, and a dust Personal Protective Equipment: respirator. **Emergency Procedures:** NA Methods for Containment: Prevent further leakage or spillage if safe to do so. Methods for Clean Up: Avoid dust formation; clean up released material using vacuum or wet sweep and shovel to minimize generation of dust. Bag and transfer to properly labeled containers. Ventilate area and wash spill site after material pickup is complete. If product is contaminated, use PPE and containment Other: appropriate to the nature of the most toxic chemical/material in the mixture.

Section 7. HANDLING AND STORAGE

Personal Precautions:	Use appropriate PPE when handling or maintaining equipment, and wash thoroughly after handling (see Section 8).
Conditions for Safe Storage:	Keep product in original container or extinguisher. Contents may be under pressure – inspect for extinguisher rust periodically to ensure container integrity.
Incompatible Products:	Do not mix with other extinguishing agents, particularly potassium bicarbonate and sodium bicarbonate. Incompatible with strong oxidizing agents and strong acids. Do not store in high humidity. Do not combine with chlorine compounds.
	Page 4 of 12 Pages ABC

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	OSHA PEL	ACGIH TLV	DFG MAK *	EU BLV
Mono- ammonium phosphate	PNOC ^{**} Total dust, 15 mg/m ³ Respirable fraction, 5 mg/m ³	PNOC Total dust, 10 mg/m ³ Respirable fraction, 3 mg/m ³	PNOC Total dust, 4 mg/m ³ Respirable fraction, 1.5 mg/m ³	NA
Mica	6 mg/m ³	3 mg/m3		NA
Attapulgite clay	PNOC ^{**} Total dust, 15 mg/m ³ Respirable fraction, 5 mg/m ³	PNOC Total dust, 10 mg/m ³ Respirable fraction, 3 mg/m ³	PNOC Total dust, 4 mg/m ³ Respirable fraction, 1.5 mg/m ³	
Silicone oil	NR**	NR		
Calcium carbonate	PNOC Total dust, 15 mg/m ³ Respirable fraction, 5 mg/m ³	PNOC Total dust, 10 mg/m ³ Respirable fraction, 3 mg/m ³		NA
Amorphous silica	20mppcf <u>80 mg/m³</u> or % SiO ₂	10 mg/m ³	4 mg/m ³	NA
Yellow 14 pigment	NR	NR	NR	NA

*German regulatory limits **PNOC = Particulates not otherwise classified (ACGIH) also known as Particulates not otherwise regulated (OSHA) *** NR = Not Regulated. All values are 8 hour time weighted average concentrations.

Engineering Controls:

Showers Eyewash stations Ventilation systems

Personal Protective Equipment - PPE Code E:

The need for respiratory protection is not probable during short-term exposure. During production, the manufacturer should use judgement concerning the need for PPE.





Eye/Face Protection: Skin and Body Protection: Respiratory Protection:





Tightly fitting safety goggles Wear protective gloves/coveralls If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn. Use P100 respirators for limited exposure. Use air-purifying respirator (APR) with high efficiency particulate air (HEPA) filters for prolonged

Page 5 of 12 Pages <u>ABC</u>

exposure. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. The need for respiratory protection is not likely for short-term use in well ventilated areas.

Hygiene Measures:

Good personal hygiene practices essential, such as avoiding food, tobacco products, or other hand-tomouth contact when handling. Wash thoroughly after handling.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Molecular Weight: Odor: Odorless Odor Threshold: Decomposition Temperature ^oC: 100 - 120 Freezing Point ^oC: Initial Boiling Point ^oC: **Physical State:** pH: Flash Point ^oC: None Autoignition Temperature ^oC: None Boiling Point/Range ^oC: Melting Point/Range ^oC: Flammability/Explosion Limits in Air ^oC: **Explosive Properties:** None **Oxidizing Properties:** None Volatile Component (%vol) **Evaporation Rate:** Vapor Density: Vapor Pressure: Specific gravity at 25 °C: Solubility: Partition Coefficient: Viscosity: NOTE: NH4H2PO4 - Monoammonium Phosphate

Light yellow powder, finely divided odorless solid NH4H2PO4: 115.03 No information available No information available No information available **Crystalline Powder** Approximately 4.4 to 4.9 No information available NH4H2PO4: 190 Upper – None; Lower-None Not applicable No information available No information available NH4H2PO4: 1.41 mm/Hg NH4H2PO4: 1.80 40.4 g/100 ml

NH4H2PO4 Est: -4.11 No information available

Page 6 of 12 Pages ABC

Section 10. STABILITY AND REACTIVITY

Stability:

Incompatibles:

Conditions to Avoid: Hazardous Decomposition Products:

Possibility of Hazardous Reactions: Hazardous Polymerization Stable under recommended storage and handling conditions. Strong oxidizing agents; Strong acids; sodium hypochlorite and chlorine compounds. Protect from moisture Storage or handling near incompatibles. Carbon, nitrogen, and potassium oxides. Heat of fire may release carbon monoxide. None Does not occur

Section 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Symptoms: Inhalation: Eyes: Skin: Acute Toxicity: Chronic Toxicity: Short-term Exposure: Long-term Exposure: Inhalation, skin and eye contact.

Irritation, coughing. Irritation. Irritation. Relatively non-toxic.

None known. As with all dusts, pneumoconiosis, or "dusty lung" disease, may result from chronic exposure.

Acute Toxicity Values - Health

Chemical Name		LD50	LC50 (Inhalation)
	Oral	Dermal	
Mono-ammonium phosphate	5750 mg/kg (rat)	>7940 mg/kg (rabbit)	Not available
Mica	None	None	None
Attapulgite clay	None	None	None
Silicone oil	None	None	None
Calcium carbonate	6450 mg/kg (rat)	500 mg/24 hr (rabbit)	Not available
Amorphous silica	>5000 mg/kg (rat)	>2000 mg/kg (rabbit)	>2.2 mg/L (rat)
Yellow 14 pigment	>17000 mg/kg (rat)	>3000 mg/kg (rat)	>4448 mg/m3 (rat)

Reproductive Toxicity:

Target Organs and Effects (TOST):

This product's ingredients are not known to have reproductive or teratogenic effects. Respiratory system (mild irritant).

This product is a mild irritant to epithelial tissue, (eyes, mucous membranes, skin) and may aggravate dermatitis. No information was found indicating the product causes sensitization.

Page 7 of 12 Pages ABC

Other Toxicity Categories

Chemical Name	Germ Cell Mutagenicity	Carcino- genicity	Repro- ductive	TOST Single Exp	TOST Repeated Exp	Aspiration
Mono-ammonium phosphate	None	None	None	Cat 3	None	None
Attapulgite clay	None	None	None	None	None	None
Mica	None	None	None	None	None	None
Silicone oil	None	None	None	None	None	None
Calcium carbonate	None	None	None	None	None	None
Amorphous silica	None	None	None	None	None	None
Yellow 14 pigment	None	None	None	None	None	None

Section 12. ECOLOGICAL INFORMATION

Ecotoxicity:	Negative effects unknown. Provides nutrient nitrogen and phosphorus to plant life.
Persistence/Degradability:	Degrades rapidly in humid/wet environment.
Probability of rapid biodegradation:	NH4H2PO4 Est: 0.693 (Rapid);
	(NH4)2SO4: Est: 0.684 (Rapid)
Anaerobic biodegradation probability:	NH4H2PO4 Est: 0.398 (Slow);
	(NH4)2SO4: Est: 0.398 (Slow)
Bioaccummulation potential:	Low.
Bioconcentration factor:	NH4H2PO4: 3.16 L/kg (wet weight) (Low BCF)
Bioaccummulation factor:	NH4H2PO4: 63.04 L/kg (wet weight)
Mobility in soil:	Slow evaporation rate; water soluble, may leach to groundwater
Log Koc:	NH4H2PO4 Est: -1.25
Log Koa:	NH4H2PO4 Est: 16.72
Log Kaw:	NH4H2PO4 Est: -20.86
NOTE: NH4H2PO4 – Mono-ammonium	Phosphate

Other Adverse Ecological Effects:

No other known effects at this time

Aquatic Toxicity Values – Environment – Research

Aquate reviewy values Environment Resourch				
Chemical Name	Acute (LC50)	Chronic (LC50)		
Mono-ammonium phosphate	N/A	N/A		
Mica	N/A	N/A		
Attapulgite clay	N/A	N/A		
Silicone oil	N/A	N/A		
Calcium carbonate	N/A	N/A		
Amorphous silica	N/A	N/A		
Yellow 14 pigment	N/A	N/A		

Aquatic Toxicity Values – Environment – Estimates

Chemical Name	Acute (LC50)	EC50
Mono-ammonium phosphate	2,91e+07 mg/L Fish 96 hr; 9.4e+06 mg/l Daphnid 48 hr;	6.70e+05 mg/L Gr. Algae 96 hr
Mica	N/A	N/A
Attapulgite clay	N/A	N/A
Silicone oil	N/A	N/A
Calcium carbonate	N/A	N/A
Amorphous silica	N/A	N/A
Yellow 14 pigment	N/A	N/A

Section 13. DISPOSAL CONSIDERATIONS

Safe Handling

Waste Disposal Considerations

Contaminated Packaging

Use appropriate PPE when handling, and wash thoroughly after handling (see Section 8). Dispose in accordance with federal, state, and local regulations. Dispose in accordance with federal, state, and local regulations.

NOTES:

This product is not a RCRA characteristically hazardous or listed hazardous waste. Dispose of according to state or local laws, which may be more restrictive than federal laws or regulations. Used product may be altered or contaminated, creating different disposal considerations.

Section 14. TRANSPORT INFORMATION

UN Number: UN Proper Shipping Name: Transport Hazard Class: Packing Group: Marine Pollutant?:	NA NA NA NO
ΙΑΤΑ	Not regulated
DOT NOTES:	Not regulated

This product is not defined as a hazardous material under U.S. Department of Transportation (DOT) 49 CFR 172, or by Transport Canada "Transportation of Dangerous Goods" regulations.

Special Precautions for Shipping:

The transportation information above covers the ABC 555 dry chemical extinguisher agent as shipped in bulk containers and not when contained in fire extinguishers or fire extinguisher systems. If shipped in a stored pressure-type fire extinguisher, and pressurized with a non-flammable, non-toxic inert expellant gas, the fire extinguisher is considered a hazardous material by the US Department of Transportation and Transport Canada. The proper shipping name shall be FIRE EXTINGUISHER and the UN designation is UN 1044. The DOT hazard class/division is LIMITED QUANTITY when pressurized to less than 241 psig and when shipped via highway or rail. UN Class 2.2. Non-Flammable Gas, when shipping via air. Packing Group – N/A

Section 15. REGULATORY INFORMATION

International Inventory Status:	All ingredients are on the following inventories	
Country(ies)	Agency	Status
United States of America	TSCA	Yes
Canada	DSL	Yes
Europe	EINECS/ELINCS	Yes
Australia	AICS	Yes
Japan	MITI	Yes
South Korea	KECL	Yes

REACH Title XVII Restrictions:

No information available

Chemical Name	Dangerous Substances	Organic Solvents	Harmful Substances Whose Names Are to be Indicated on Label	Pollution Release and Transfer Registry (Class II)	Pollution Release and Transfer Registry (Class I)	Poison and Deleterious Substances Control Law
Monoammonium Phosphate	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Component	ISHA – Harmful Substances Prohibited for Manufacturing, Importing, Transferring, or Supplying	ISHA – Harmful Substances Requiring Permission	Toxic Chemical Classification Listing (TCCL) – Toxic Chemicals	Toxic Release Inventory (TRI) – Group I	Toxic Release Inventory (TRI) – Group II
Monoammonium Phosphate 7722-76-1	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Attapulgite clay 12174-11-7 (>3)	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Mica- potassium aluminum silicate 120001-26-2 (>2)	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Calcium carbonate 471-34-1	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Amorphous silica 69012-64-2	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Yellow 14 pigment 5468-75-7	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

European Risk and Safety phrases:

EU Classification: Xi	n - Irritant	
R Phrases:	20	Harmful by inhalation.
	36/37/38	Irritating to eyes, respiratory system and skin.
S Phrases:	22	Do not breath dust.
	24/25	Avoid contact with skin and eyes
	26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	36	Wear suitable protective clothing.

U.S. Federal Regulatory Information:

SARA 313:

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) - This product does not contain and chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

None of the chemicals in this product are under SARA reporting requirements or have SARA threshold planning quantities (TPQs) or CERCLA reportable quantities (RQs), or are regulated under TSCA 8(d).

SARA 311/312 Hazard Categories:

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
*-Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

* - Only applicable if material is in a pressurized extinguisher.

Clean Water/Clean Air Acts:

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42) or Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61) and Section 112 of the Clean Air Act Amendments of 1990.

U.S. State Regulatory Information:

Chemicals in this product are covered under specific State regulations, as denoted below:

Alaska - Designated Toxic and Hazardous Substances: None California – Permissible Exposure Limits for Chemical Contaminants: None Florida – Substance List: Mica Dust Illinois – Toxic Substance List: None Kansas – Section 302/303 List: None Massachusetts – Substance List: Mica Dust Minnesota – List of Hazardous Substances: None Missouri – Employer Information/Toxic Substance List: None New Jersey – Right to Know Hazardous Substance List: None North Dakota – List of Hazardous Chemicals, Reportable Quantities: None Pennsylvania – Hazardous Substance List: None Rhode Island – Hazardous Substance List: Mica Dust Texas – Hazardous Substance List: No West Virginia – Hazardous Substance List: None Wisconsin – Toxic and Hazardous Substances: None

California Proposition 65: No component is listed on the California Proposition 65 list.

<u>Other</u>: Mexico – Grade Canada – WHMIS Hazard Class

No component listed No component listed

Section 16. OTHER INFORMATION

This SDS conforms to requirements under U.S., U.K., Canadian, Australian, and EU regulations or standards, and conforms to the proposed 2003 ANSI Z400.1 format.

Issuing Date Revision Date Revision Notes 17-June-2012 13-March-2018 None

The information herein is given in good faith but no warranty, expressed or implied, is made. Updated by William F. Garvin, CIH.



Version 1.2	Revision Date: 03/19/2015		SDS Number: 3955-00003	Date of last issue: 02/10/2015 Date of first issue: 01/13/2015
SECTION	1. IDENTIFICATION			
Produ	Product name		PURELL® Hand	Sanitizer
Manu	facturer or supplier's	deta	ails	
			GOJO Industries,	Inc.
Addre	SS	:	One GOJO Plaza Akron OH 44311	a, Suite 500
Telep	hone	: 1 (330) 255-6000		
Emerg	gency telephone	: 1-800-424-9300 (CHEMTREC
Reco	mmended use of the o	cher	nical and restriction	ons on use
Recor	mmended use	:	Hand Sanitizer	
Restri	ctions on use	:	consumers and o foreseeable use. specifically define exempt from the While this materia contains valuable proper use of the as well as unusua spills. This SDS s employees and o intended-use guid	I care or cosmetic product that is safe for ther users under normal and reasonably Cosmetics and consumer products, ed by regulations around the world, are requirement of an SDS for the consumer. al is not considered hazardous, this SDS information critical to the safe handling and product for industrial workplace conditions al and unintended exposures such as large should be retained and available for ther users of this product. For specific dance, please refer to the information ackage or instruction sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Flammable liquids	: Category 3
Eye irritation	: Category 2A
GHS Label element Hazard pictograms	
Signal Word	: Warning
Hazard Statements	: H226 Flammable liquid and vapor. H319 Causes serious eye irritation.



Version	Revision Date:	MSDS Number:	Date of last issue: 02/10/2015
1.2	03/19/2015	46955-00003	Date of first issue: 01/13/2015
Preca	autionary Statements	No smoking. P233 Keep cont P241 Use explo equipment. P242 Use only r P243 Take pred P264 Wash skir P280 Wear prot Response: P303 + P361 + all contaminated P305 + P351 + for several minut to do. Continue P337 + P313 If attention. Storage: P403 + P235 St Disposal:	ay from heat/sparks/open flames/hot surfaces. tainer tightly closed. osion-proof electrical/ ventilating/ lighting/ non-sparking tools. cautionary measures against static discharge. In thoroughly after handling. tective gloves/ eye protection/ face protection. P353 IF ON SKIN (or hair): Take off immediately d clothing. Rinse skin with water/shower. P338 IF IN EYES: Rinse cautiously with water ites. Remove contact lenses, if present and easy rinsing. eye irritation persists: Get medical advice/ tore in a well-ventilated place. Keep cool.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Ethanol	64-17-5	>= 50 - < 70
Propan-2-ol	67-63-0	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice	In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medic advice.	cal
If inhaled	If inhaled, remove to fresh air. Get medical attention if symptoms occur.	
In case of skin contact	Wash with water and soap as a precaution. Get medical attention if symptoms occur.	
In case of eye contact	In case of contact, immediately flush eyes with plenty of wa for at least 15 minutes. If easy to do, remove contact lens, if worn.	ıter



Version 1.2	Revision Date: 03/19/2015	MSDS Number: 46955-00003	Date of last issue: 02/10/2015 Date of first issue: 01/13/2015
lf sw	allowed	Get medical a	ttention. DO NOT induce vomiting. ttention if symptoms occur. horoughly with water.
	t important symptoms effects, both acute and yed	: Causes seriou	s eye irritation.
Prote	ection of first-aiders	and use the re	onders should pay attention to self-protection, commended personal protective equipment ntial for exposure exists.
Note	s to physician	: Treat sympton	natically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Carbon oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
Environmental precautions	: Discharge into the environment must be avoided.



Version 1.2	Revision Date: 03/19/2015	MSDS Number: 46955-00003	Date of last issue: 02/10/2015 Date of first issue: 01/13/2015
		Prevent spreadi barriers). Retain and disp Local authorities cannot be conta	
Methods and materials for : containment and cleaning up		Soak up with ine Suppress (knocl jet. For large spills, containment to k can be pumped, container. Clean up remain absorbent. Local or national disposal of this n employed in the determine which Sections 13 and	ols should be used. ert absorbent material. k down) gases/vapors/mists with a water spray provide diking or other appropriate keep material from spreading. If diked material store recovered material in appropriate hing materials from spill with suitable I regulations may apply to releases and material, as well as those materials and items cleanup of releases. You will need to h regulations are applicable. I 15 of this SDS provide information regarding mational requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures	: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	: Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.
Advice on safe handling	 Do not breathe vapors or spray mist. Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	 Keep in properly labeled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
Materials to avoid	: Do not store with the following product types: Strong oxidizing agents



Version	Revision Date:	MSDS Number:	Date of last issue: 02/10/2015
1.2	03/19/2015	46955-00003	Date of first issue: 01/13/2015
		•	s s stances and mixtures mixtures which in contact with water emit

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1

Ingredients with workplace control parameters

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentratio n	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI

Engineering measures

: Minimize workplace exposure concentrations. Use only in an area equipped with explosion proof exhaust ventilation. Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and



Version 1.2	Revision Date: 03/19/2015		SDS Number: 955-00003	Date of last issue: 02/10/2015 Date of first issue: 01/13/2015
			by air purifying reachazardous chemic supplied respirator release, exposure	A approved respirators. Protection provided spirators against exposure to any cal is limited. Use a positive pressure air or if there is any potential for uncontrolled e levels are unknown, or any other ere air purifying respirators may not provide on.
	d protection aterial	:	Impervious gloves	S
M	aterial	:	Flame retardant g	loves
Re	emarks	:	on the concentrat time is not determ For special applic resistance to cher	protect hands against chemicals depending ion specific to place of work. Breakthrough nined for the product. Change gloves often! ations, we recommend clarifying the micals of the aforementioned protective ove manufacturer. Wash hands before end of workday.
Eye	protection	:	Wear the following Safety goggles	g personal protective equipment:
Skin	and body protection	:	resistance data an potential. Wear the following Flame retardant a Skin contact must	e protective clothing based on chemical nd an assessment of the local exposure g personal protective equipment: antistatic protective clothing. t be avoided by using impervious protective aprons, boots, etc).
Hygi	ene measures	:	located close to the When using do not	lushing systems and safety showers are ne working place. ot eat, drink or smoke. ed clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: clear, Colorless to pale yellow
Odor	: citrus
Odor Threshold	: No data available
рН	: 6.0 - 9.2
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available



Vers 1.2	sion	Revision Date: 03/19/2015		DS Number: 55-00003	Date of last issue: 02/10/2015 Date of first issue: 01/13/2015
	Flash p	oint	:	25 °C	
	Evapor	ation rate	:	No data available	
	Flamma	ability (solid, gas)	:	Not applicable	
	Upper e	explosion limit	:	No data available	
	Lower e	explosion limit	:	No data available	
	Vapor p	pressure	:	No data available	
	Relative	e vapor density	:	No data available	
	Density	,	:	0.89 g/cm3	
	Solubili Wate	ty(ies) er solubility	:	soluble	
	Partition octanol	n coefficient: n- /water	:	Not applicable	
	Autoign	ition temperature	:	No data available	
	Decom	position temperature	:	The substance or	mixture is not classified self-reactive.
	Viscosi [.] Visco	ty osity, kinematic	:	1,000 - 35,000 m	m2/s (20 °C)
	Explosi	ve properties	:	Not explosive	
	Oxidizir	ng properties	:	The substance or	mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac- tions	 Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.





Version 1.2	Revision Date: 03/19/2015		DS Number: 955-00003	Date of last issue: 02/10/2015 Date of first issue: 01/13/2015
SECTION	11. TOXICOLOGICAI	L INFC	RMATION	
Inhala Skin o Inges	contact	es of e	xposure	
Acute	e toxicity			
Not c	lassified based on ava	ilable i	nformation.	
Prod				
Acute	e oral toxicity	:	Acute toxicity of Method: Calcu	estimate: > 5,000 mg/kg lation method
<u>Ingre</u> Ethai	dients:			
	e oral toxicity	:	LD50 (Rat): >	5,000 mg/kg
Acute	inhalation toxicity	:	LC50 (Rat): 12 Exposure time Test atmosphe	:4h
	an-2-ol: e oral toxicity	:	LD50 (Rat): >	5,000 mg/kg
Acute	inhalation toxicity	:	LC50 (Rat): 72 Exposure time Test atmosphe	: 4 h
Acute	e dermal toxicity	:	LD50 (Rat): >	5,000 mg/kg
Skin	corrosion/irritation			
Not c	lassified based on ava	ilable i	nformation.	
Prod	uct:			
Resu	lt: No skin irritation			

Ingredients:

Ethanol: Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

Propan-2-ol:

Species: Rabbit Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Ingredients:



Version	Revision Date:	MSDS Number:
1.2	03/19/2015	46955-00003

Date of last issue: 02/10/2015 Date of first issue: 01/13/2015

Ethanol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days Method: OECD Test Guideline 405

Propan-2-ol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

Ingredients:

Ethanol:

Test Type: Local lymph node assay (LLNA) Routes of exposure: Skin contact Species: Mouse Result: negative

Propan-2-ol:

Test Type: Buehler Test Routes of exposure: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Ethanol: Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Ingestion Result: negative
Propan-2-ol: Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative





Version 1.2	Revision Date: 03/19/2015	MSDS Number: 46955-00003	Date of last issue: 02/10/2015 Date of first issue: 01/13/2015
Carc	inogenicity		
Not c	classified based on availa	ble information.	
Prop Spec Appli Expo Meth	edients: pan-2-ol: cies: Rat cation Route: inhalation (psure time: 104 weeks od: OECD Test Guideline ult: negative		
IAR	0		product present at levels greater than or ntified as probable, possible or confirmed by IARC.
OSH	IA		product present at levels greater than or ntified as a carcinogen or potential carcino-
NTP		No ingredient of this product present at levels greater th equal to 0.1% is identified as a known or anticipated car by NTP.	
-	oductive toxicity classified based on availa	ble information.	
Ingre	edients:		
Etha Effec	nol: ets on fertility	Species: Mouse Application Route	generation reproduction toxicity study e: Ingestion Test Guideline 416
Pron	an-2-ol:		
•	ets on fertility	: Test Type: Two- Species: Rat Application Route Result: negative	generation reproduction toxicity study e: Ingestion
Effec	ts on fetal development	: Test Type: Embr Species: Rat Application Route Result: negative	yo-fetal development e: Ingestion
	T-single exposure classified based on availa	ble information	
	edients:		

Propan-2-ol:

Assessment: May cause drowsiness or dizziness.



Version	Revision Date:	MSDS Number:
1.2	03/19/2015	46955-00003

Date of last issue: 02/10/2015 Date of first issue: 01/13/2015

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Ingredients:

Ethanol: Species: Rat NOAEL: 2,400 mg/kg Application Route: Ingestion Exposure time: 2 y

Propan-2-ol:

Species: Rat NOAEL: 5000 ppm Application Route: inhalation (vapor) Exposure time: 104 w Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients: Ethanol: Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d
Toxicity to bacteria	:	EC50 (Photobacterium phosphoreum): 32.1 mg/l Exposure time: 0.25 h
Propan-2-ol: Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to algae	:	ErC50 (Scenedesmus quadricauda (Green algae)): > 1,800 mg/l



sion	Revision Date: 03/19/2015	MSDS Number: 46955-00003	Date of last issue: 02/10/2015 Date of first issue: 01/13/2015
		Exposure tim	e: 8 d
Toxic	ity to bacteria	: EC50 (Pseud Exposure tim	omonas putida): > 1,050 mg/l e: 16 h
Persi	stence and degrada	bility	
	dients:		
Ethar Biode	iol: gradability	: Result: Readi Biodegradatio Exposure tim	
	a n-2-ol: gradability	: Result: rapidl	y degradable
Bioaccumulative potential		ıl	
	dients:		
	nol: on coefficient: n- ol/water	: log Pow: -0.3	5
Propa	an-2-ol:		
	on coefficient: n- ol/water	: log Pow: 0.05	
Mobil	lity in soil		
No da	ıta available		
Other	adverse effects		
No da	ita available		

Disposal methods Waste from residues	: Dispose of in accordance with local regulations.
Contaminated packaging	 Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulation

UN number	:	UN 1987
Proper shipping name	:	ALCOHOLS, N.O.S.



Versio 1.2	on	Revision Date: 03/19/2015		SDS Number: 955-00003	Date of last issue: 02/10/2015 Date of first issue: 01/13/2015		
				(Ethanol, Propan-	-2-ol)		
-	Class			3			
		g group					
L	Labels		:	3			
ί	I ATA-E UN/ID Proper			UN 1987 Alcohols, n.o.s.			
		oppg		(Ethanol, Propan-	-2-ol)		
C	Class		:	· ·	,		
F	Packin	g group	:	III			
_	Labels		: Flammable Liquids				
	Packin aircraft	g instruction (cargo	:	366			
F	Packin	g instruction nger aircraft)	:	355			
I	IMDG-	Code					
	UN nur			UN 1987			
F	Proper	shipping name	:	ALCOHOLS, N.O (Ethanol, Propan-			
-	Class			3	,		
		g group	:				
	Labels EmS C	ode.	:	3 F-E, S-D			
		pollutant	:	no			
r	Transp	oort in bulk accordin	g to	Annex II of MARP	OL 73/78 and the IBC Code		
	-	plicable for product as	-				
-	D a						
	Domes	stic regulation					

49 CFR
UN/ID/NA number: UN 1987
Proper shipping nameClass: ALCOHOLS, N.O.S.Class: JPacking group: III
LabelsLabels: FLAMMABLE LIQUID
ERG CodeERG Code: 127
no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard



ersion 2	Revision Date: 03/19/2015	MSDS N 46955-0		Date of last issue: 02/10/2 Date of first issue: 01/13/2		
		Acut	e Health Ha	zard		
SAR	A 302			this material are subject to tl SARA Title III, Section 302.	ne reporting	
SARA 313			The following components are subject to reporting levels established by SARA Title III, Section 313:			
		Prop	an-2-ol	67-63-0	3.013 %	
US St	tate Regulations					
Penn	sylvania Right To Kr	ow				
	Ethanol			64-17-5	50 - 70 %	
	Water			7732-18-5	30 - 50 %	
	Propan-2-	bl		67-63-0	1 - 5 %	
New .	Jersey Right To Kno	w				
	Ethanol			64-17-5	50 - 70 %	
	Water			7732-18-5	30 - 50 %	
	Propan-2-	bl		67-63-0	1 - 5 %	
California Prop 65		State		es not contain any chemicals ia to cause cancer, birth, or a ects.		

AICS


: All ingredients listed or exempt.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)



Version 1.2			Date of last issue: 02/10/2015 Date of first issue: 01/13/2015	
SECTION	16. OTHER INFORM	IATION		
Furth	er information			
NFPA	A:		HMIS III:	





0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH ACGIH BEI NIOSH REL	:	USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI) USA. NIOSH Recommended Exposure Limits
OSHA Z-1		USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-
	•	its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average
Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/
Revision Date	:	03/19/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8