

Safety Data Sheets

Public Defender



Old Admin, Bisbee

11/26/2019



Safety Data Sheet Index
Binder: Old Admin, Bisbee - Public Defender

Product Name	CAS Number	Manufacturer	Version Date	Page
LYSOL BRAND DISINFECTANT SPRAY - ALL SCENTS - LYSOL BRAND DISINFECTANT SPRAY - ALL SCENTS		L & F PRODUCTS	09/30/1994	3
Poli-Kleen Wax Polish - Poli-Kleen Wax Polish		WAXIE SANITARY SUPPLY	08/29/2012	8

[Return to Index](#)

MATERIAL SAFETY DATA SHEET

LYSOL(R*) BRAND DISINFECTANT SPRAY - ALL SCENTS

REV. DATE: 09/30/94

L & F PRODUCTS
225 SUMMIT AVENUE
MONTVALE, NJ 07645

TELEPHONE NUMBER: (201)573-5700 (24 HRS)

EMERGENCY CONTACT: CHEMTREC-FOR DOT EMERGENCIES ONLY

EMERGENCY PHONE NUMBER: (800)424-9300

-----SECTION #1 - IDENTIFICATION -----

PRODUCT: LYSOL(R*) BRAND DISINFECTANT SPRAY - ALL SCENTS

EPA REG. NO.: 777-53

SPECIAL HAZARDS: FLAMMABLE. CONTENTS UNDER PRESSURE.

HAZARD RATINGS:

NFPA

HEALTH: 1 SLIGHT

FIRE: LEVEL 1 AEROSOL

REACTIVITY: 0 NEGLIGIBLE

HMIS

HEALTH: 1 SLIGHT

FLAMMABILITY: 3 SERIOUS*

REACTIVITY: 0 MINIMAL

*THIS IS A LEVEL 1 AEROSOL. THIS RATING APPLIES TO THE PRODUCT CONCENTRATE
AND NOT THE FINISHED, SEALED AEROSOL PRODUCT.

PRODUCT DESCRIPTION: AEROSOL DISINFECTANT

FORMULA NO.	PRODUCT NO.	SCENT
Z2381	01-C0111-000	ORIGINAL
56-036	01-C0508-000	ORIGINAL
4Z1961	01-C0115-000	FRESH
73-004	01-C0505-000	FRESH
7Z1511	01-C0123-000	FRESH
8Z0531	01-C0131-000	LIGHT (I.C.)
3AB1122	01-C0134-000	LIGHT (I.C.)
Z047A-10	01-C0144-000	COUNTRY
76-054B	01-C0673-000	COUNTRY
AE3-090B	01-C0335-000	MOUNTAIN
75-013B	01-C0339-000	MOUNTAIN
75-018	01-C0736-000	BAYBERRY PINE

THIS PRODUCT IS A REGISTERED PESTICIDE. USE OF THIS PRODUCT IN A MANNER NOT
CONSISTENT WITH THE LABEL INSTRUCTIONS IS A VIOLATION OF FEDERAL LAW.

-----SECTION #2 - HAZARDOUS CHEMICAL COMPONENTS -----

[Return to Index](#)

COMPONENT: CARBON DIOXIDE (AS PROPELLANT)

CAS NUMBER: 124-38-9 PERCENT OF MIXTURE: 4.0
ACGIH TLV-STEL: 30,000 PPM
ACGIH TLV-TWA: 5000 PPM
OSHA PEL-TWA: 5,000 PPM

COMPONENT: ETHANOL

CAS NUMBER: 64-17-5 PERCENT OF MIXTURE: 79.0
ACGIH TLV-TWA: 1000 PPM
OSHA PEL-TWA: 1000 PPM

COMPONENT: ORTHO-PHENYLPHENOL

CAS NUMBER: 90-43-7 PERCENT OF MIXTURE: .1
NO EXPOSURE LIMITS ESTABLISHED
BY ACGIH OR OSHA

-----SECTION #3 - PHYSICAL DATA -----

BOILING POINT: NOT APPLICABLE DEG C

VAPOR PRESSURE: 95 - 105 PSIG

VAPOR DENSITY (AIR=1): >1

SPECIFIC GRAVITY: 0.835 @ 25 DEG C (CONC)

SOLUBILITY (H2O): COMPLETE

PH: APPROX. 10 AT A CONCENTRATION OF: 50%

APPEARANCE:

AEROSOL CONTAINER

-----SECTION #4 - FIRE FIGHTING & EXPLOSION DATA -----

FLASH POINT: 70 DEG F TCC (CONCENTRATE)

LOWER EXPLOSIVE LIMIT (%): NOT DETERMINED

UPPER EXPLOSIVE LIMIT (%): NOT DETERMINED

FIRE AND EXPLOSION HAZARDS

FLAMMABLE. CONTENTS UNDER PRESSURE. DO NOT USE NEAR HEAT, SPARK OR FLAME.
DO NOT PUNCTURE OR INCINERATE CONTAINER. EXPOSURE TO TEMPERATURES ABOVE 130
DEG F MAY CAUSE BURSTING.

EXTINGUISHING MEDIA

WATER SPRAY, FOAM, DRY CHEMICAL OR CARBON DIOXIDE. USE MEDIA SUITABLE FOR
SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

SPECIAL FIRE FIGHTING INSTRUCTIONS

WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE EQUIPMENT
APPROPRIATE FOR FIGHTING A TYPICAL CHEMICAL FIRE. MOVE CONTAINERS AWAY FROM
FIRE IF POSSIBLE AND SAFE TO DO SO. USE WATER SPRAY TO COOL FIRE EXPOSED
CONTAINERS. PROVIDE SHIELDING FOR VENTING, RUPTURING OR BURSTING
CONTAINERS.

-----SECTION #5 - EXPOSURE EFFECTS AND FIRST AID -----

[Return to Index](#)

ROUTE OF EXPOSURE - INHALATION:

NONE EXPECTED. SUSCEPTIBLE INDIVIDUALS MAY EXPERIENCE DIZZINESS, DROWSINESS, NAUSEA AND VOMITING IF EXPOSED TO EXTREMELY HIGH CONCENTRATIONS OF THE VAPORS.

FIRST AID - INHALATION:

IF REQUIRED, REMOVE TO FRESH AIR.

ROUTE OF EXPOSURE - SKIN:

NONE EXPECTED.

FIRST AID - SKIN:

RINSE WITH WATER.

ROUTE OF EXPOSURE - EYES:

AVOID CONTACT WITH EYES.

FIRST AID - EYES:

IMMEDIATELY FLUSH EYES THOROUGHLY WITH WATER, REMOVE ANY CONTACT LENSES AND CONTINUE TO FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

ROUTE OF EXPOSURE - INGESTION:

INGESTION IS VERY UNLIKELY THROUGH THE NORMAL ANTICIPATED USE OF THIS PRODUCT. INGESTION OF SMALL QUANTITIES IS NOT EXPECTED TO CAUSE ANY SIGNIFICANT ADVERSE EFFECTS. AVOID CONTACT WITH FOOD.

FIRST AID - INGESTION:

CONTACT A PHYSICIAN.

MISCELLANEOUS TOXICOLOGICAL INFORMATION:

CARCINOGENICITY: NTP: NO IARC: NO OSHA: NO

HEALTH CONDITIONS AGGRAVATED BY EXPOSURE:

NONE KNOWN

-----SECTION #6 - REACTIVITY & POLYMERIZATION -----

STABILITY: STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID TEMPERATURES ABOVE 130 DEG F

INCOMPATIBLE MATERIALS:

STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING THERMAL DECOMPOSITION.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

-----SECTION #7 - SPILL, LEAK, & DISPOSAL PROCEDURES -----

STEPS TO BE TAKEN IN THE EVENT OF SPILLS, LEAKS, OR RELEASE:

FOR LARGE SPILLS DUE TO RUPTURED CONTAINERS, ELIMINATE ALL SOURCES OF IGNITION AND VENTILATE THE AREA WITH EQUIPMENT RATED FOR USE IN FLAMMABLE

[Return to Index](#)

ENVIRONMENT. COLLECT LIQUID AND STORE IN METAL CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHODS:

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

CONTAINER DISPOSAL:

REPLACE CAP AND DISCARD IN TRASH. DO NOT PUNCTURE OR INCINERATE. DO NOT REUSE EMPTY CONTAINER.

OTHER ENVIRONMENTAL INFORMATION:

NONE OF THE INGREDIENTS IN THIS PRODUCT MEET THE REPORTING REQUIREMENTS OF THE SARA TITLE III, SECTION 313 LIST OF TOXIC CHEMICALS.

-----SECTION #8 - SPECIAL PROTECTIVE MEASURES -----

VENTILATION: NONE REQUIRED.

EYE PROTECTION: NONE REQUIRED.

SKIN PROTECTION: NONE REQUIRED.

RESPIRATORY PROTECTION: NONE REQUIRED.

-----SECTION #9 - SPECIAL PRECAUTIONS - STORAGE & HANDLING -----

STORAGE & HANDLING CONDITIONS:

STORE IN ORIGINAL CONTAINER IN AREAS INACCESSIBLE TO SMALL CHILDREN.
FLAMMABLE. CONTENTS UNDER PRESSURE. DO NOT USE NEAR FIRE, SPARKS OR FLAME.
EXPOSURE TO TEMPERATURES ABOVE 130 DEG F MAY CAUSE BURSTING.

-----SECTION #10 - SHIPPING INFORMATION -----

PROPER SHIPPING NAME: CONSUMER COMMODITY

HAZARD CLASS: ORM-D DOMESTIC COMMERCE - SURFACE ONLY

STATE REGULATED COMPONENTS

COMPONENT: CARBON DIOXIDE (AS PROPELLANT)

CAS NUMBER: 124-38-9 PERCENT OF MIXTURE: 4.0

STATE REGULATIONS: ILL MAS NJW PAW

COMPONENT: ETHANOL

CAS NUMBER: 64-17-5 PERCENT OF MIXTURE: 79.0

STATE REGULATIONS: ILL MAS NJS NJW PAW P65

COMPONENT: ORTHO-PHENYLPHENOL

CAS NUMBER: 90-43-7 PERCENT OF MIXTURE: .1

STATE REGULATIONS: NJE NJW

ILL - ILLINOIS TOXIC SUBSTANCE

MAS - MASSACHUSETTS HAZARDOUS SUBSTANCE

NJE - NEW JERSEY ENVIRONMENTAL HAZARDOUS SUBSTANCE

NJS - NEW JERSEY SPECIAL HEALTH HAZARDOUS SUBSTANCE

NJW - NEW JERSEY WORKPLACE HAZARDOUS SUBSTANCE

PAE - PENNSYLVANIA ENVIRONMENTAL HAZARDOUS SUBSTANCE

[Return to Index](#)

PAS - PENNSYLVANIA SPECIAL HAZARDOUS SUBSTANCE
PAW - PENNSYLVANIA WORKPLACE HAZARDOUS SUBSTANCE
P65 - CALIFORNIA PROPOSITION 65

MATERIAL SAFETY DATA SHEET

Poli-Kleen Wax Polish

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Poli-Kleen Wax Polish
Product Number: A00136
Product Use: Polishing wax.
Manufacturer/Supplier: Waxie Sanitary Supply
9353 Waxie Way
San Diego, CA 92193-1036
Phone Number: 1-800-995-4466
D.O.T. Emergency Phone: 1-800-255-3924 CHEMTEL 24 HR
Date of Preparation: August 29, 2012 **Revision #:** 2.0

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS: See Section 15

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED. HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.

Skin: May cause skin irritation.

Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed.

Inhalation: May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Handling can cause dry skin.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Distillates (petroleum), hydrotreated light	64742-47-8	5 - 10
Isobutane	75-28-5	1 - 5
Propane	74-98-6	1 - 5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	0.1 - 1
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	0.1 - 1

MATERIAL SAFETY DATA SHEET

Poli-Kleen Wax Polish

Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water. If easy to do, remove contact lenses, if worn.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- Inhalation:** If breathed in, move person into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).
- Note to Physicians:** Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

- Flammability:** Not flammable by OSHA criteria.
- Means of Extinction:**
- Suitable Extinguishing Media:** Powder, foam, carbon dioxide.
 - Unsuitable Extinguishing Media:** Water.
- Products of Combustion:** May include, and are not limited to: oxides of carbon.
- Explosion Data:**
- Sensitivity to Mechanical Impact:** Not available.
 - Sensitivity to Static Discharge:** Not available.
- Protection of Firefighters:** Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.
- Environmental Precautions:** Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
- Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for Clean-Up:** Vacuum or sweep material and place in a disposal container. Allow gas to dissipate harmlessly into the atmosphere.
- Other Information:** Not available.

MATERIAL SAFETY DATA SHEET

Poli-Kleen Wax Polish

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Do not store at temperatures above 49 °C / 120 °F.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Distillates (petroleum), hydrotreated light	100 ppm	200 mg/m ³
Isobutane	Not available.	1000 ppm
Propane	1000 ppm	1000 ppm
Distillates (petroleum), hydrotreated light naphthenic	5 mg/m ³ (mist)	5 mg/m ³ (mist)
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m ³ (mist)	5 mg/m ³ (mist)

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

HMIS: See Section 15

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Opaque.
Colour:	White.
Odour:	Lemon.
Odour Threshold:	Not available.
Physical State:	Gas/Pressurized Liquid.
pH:	9-11
Viscosity:	Not available.
Freezing Point:	Not available.
Boiling Point:	Not available.
Flash Point:	Not available.
Evaporation Rate:	< 1 (Water = 1)
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.

MATERIAL SAFETY DATA SHEET

Poli-Kleen Wax Polish

Vapor Pressure:	Not available.
Vapor Density:	Not available.
Specific Gravity:	0.972 (Concentrate only)
Solubility in Water:	Not available.
Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	7.2% (US federal/CARB/OTC/LADCO)
VOC content, g/L:	Not available.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Oxidizers.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD₅₀ (oral)	LC₅₀
Distillates (petroleum), hydrotreated light	> 5000 mg/kg, rat	> 5.2 mg/L 4hr, rat
Isobutane	Not available.	658 mg/L 4hr, rat
Propane	Not available.	658 mg/L 4hr, rat
Distillates (petroleum), hydrotreated light naphthenic	> 5000 mg/kg, rat	2.18 mg/L 4hr, rat
Distillates (petroleum), hydrotreated heavy naphthenic	> 5000 mg/kg, rat	> 5.0 mg/L 4hr, rat

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Handling can cause dry skin.

Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed.

Inhalation: May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by OSHA criteria.

Carcinogenicity: Not hazardous by OSHA criteria.

MATERIAL SAFETY DATA SHEET

Poli-Kleen Wax Polish

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen *
Distillates (petroleum), hydrotreated light	Not listed.
Isobutane	Not listed.
Propane	Not listed.
Distillates (petroleum), hydrotreated light naphthenic	Not listed.
Distillates (petroleum), hydrotreated heavy naphthenic	Not listed.

* See Section 15 for more information.

Mutagenicity: Not hazardous by OSHA criteria.

Reproductive Effects: Not hazardous by OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by OSHA criteria.

Embryotoxicity: Not hazardous by OSHA criteria.

Respiratory Sensitization: Not hazardous by OSHA criteria.

Skin Sensitization: Not hazardous by OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

ORM-D, Limited Quantity

Section 15: REGULATORY INFORMATION

Federal Regulations

US: MSDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200).

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Distillates (petroleum), hydrotreated light	Not listed.	Not listed.	Not listed.	Not listed.
Isobutane	Not listed.	Not listed.	Not listed.	Not listed.
Propane	Not listed.	Not listed.	Not listed.	Not listed.
Distillates (petroleum), hydrotreated light naphthenic	Not listed.	Not listed.	Not listed.	Not listed.
Distillates (petroleum), hydrotreated heavy naphthenic	Not listed.	Not listed.	Not listed.	Not listed.

MATERIAL SAFETY DATA SHEET

Poli-Kleen Wax Polish

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient

	USA TSCA
Distillates (petroleum), hydrotreated light	Yes.
Isobutane	Yes.
Propane	Yes.
Distillates (petroleum), hydrotreated light naphthenic	Yes.
Distillates (petroleum), hydrotreated heavy naphthenic	Yes.

HMIS - Hazardous Materials Identification System

Health - 2 Flammability - 2 Physical Hazard - 0 PPE – B

NFPA - National Fire Protection Association:

Health - 2 Fire - 2 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

- 1 - Known to be carcinogens.
- 2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.

Prepared for: Waxie Sanitary Supply
1-800-995-4466

